

Horse HM-RB16

Unidirectional Carbon Fiber Rebar For Strengthening

Description HM-RB16 is a high strength, high modulus unidirectional carbon fiber reinforce polymer(CFRP) for structural strengthening. It is bonded onto the structure as external reinforcement using HM-120CP epoxy resin as the

Application Range

- **Load Increase**
 - Increased live loads in warehouses
 - Increased traffic volumes on bridges
 - Installation of heavy machinery in industrial buildings
 - Vibrating structures
 - Changes of building utilization
- **Seismic Reinforcement**
 - Concrete column wrapping, beam strengthening, wall strengthening, slab strengthening
 - Masonry walls reinforcement
- **Damage to Structural Parts**
 - Aging of construction materials
 - Fire
 - Vehicle impact
- **Change of Structural System**
 - Removal of walls or columns
 - Removal of slab sections for openings
- **Design or Construction Defects**
 - Lack of reinforcing bars
 - Lack of member cross section
- **Improve Structural State**
 - Reduce the deformation
 - Reduce the stress of the original structure
 - The crack reinforcement

- Product Characteristic**
- High strength, high toughness, high modulus
 - Soft and flexible, light self weight, easy to install
 - Long shelf life and aging resistance
 - High temperature resistance
 - Acid, alkali & salt resistance
 - Seismic resistance
 - Environmental-friendly
 - Can be used for shear strengthening, confinement strengthening, flexural strengthening

Horse Advantage

■ **Aviation Grade Yarn**

Imported aviation grade raw material, excellent quality and stable performance.

■ **World Leading Production Line**

Germany imported intelligent production line. Point to point active weft insertion. No damage to the yarn during the weaving process.

excellent flatness enable epoxy easy to penetrate, hence high bonding strength can be achieved

■ **Patented Tension Controlling System**

Our own developed whole process tension controlling system. It ensures the constant tension, low dispersion.

■ **Large output and Timely Delivery**

100 thousand meters annual output.

Package

This product is rolled into a ring and uses a belt to bind. The length of the rebar is 1m, 3m or according to the request, the diameters are 8mm, 10mm, 12mm and 16mm or according to the request

Basic Information

Model	HM-RB16
Appearance	Black laminate
Length	1m, 3m or customized
Diameter	16mm
Shelf Life	50 years
Storage Conditions	Store in dry conditions at 40°F to 95°F (4°C to 35°C)
Braiding	0° (Unidirectional)

Performance indexes

Tensile Strength	
Mean Value	3.19×10 ⁵ psi (2200 MPa)
Design Value	2.90×10 ⁵ psi (2000 MPa)
Tensile Elastic Modulus	
Mean Value	2.39×10 ⁷ psi (1.65×10 ⁵ MPa)
Design Value	2.32×10 ⁷ psi (1.6×10 ⁵ MPa)
Elongation	1.80%
Thickness	1.2mm
Temperature Resistance	> 300°F (> 150°C)
Fiber volume content	≥65%
Density	0.058 lbs./in ³ (1.6g/cm ³)

Construction Process

1. Setting out according to designing;
2. Polish the surface of concrete surface to remove painting of the surface, blow out the floating dust with compressed air;
3. Prepare ingredients: agitate component A and B evenly in packaging bucket by weighting in accordance with the weight ratio A: B =2:1;
4. Installing: Past the above mixed glue compounds onto the surface of carbon fiber rebar evenly, please avoid bubbles;
5. Anchorage: paste the carbon fiber rebar onto the concrete surface and fixed with steel strip, remove excessive glue compounds around, and fix With Steel framework;
6. Maintenance: conservation time should be no less than 24 hours at room temperature.

Points for Attention

The construction workers should take necessary protective measures such as wearing masks, gloves, goggles etc. Pay attention to fire prevention and maintain good ventilation on site.

Carbon fiber material is conductive, be careful to the electrical equipments around.

For more information, please visit our website at www.horseen.com



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE